

**Serie | 2, canopy cooker hood, 53 cm,  
Stainless steel  
DLN53AA50B**



**The canopy cooker hood: offers you flexibility in your kitchen planning - mount it either on the wall or above a kitchen island.**

- **Silent:** maximal extractor performance with little noise
- **LED-Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality.
- 3-Speed Power Level Options To Suit Your Cooking Style And Recipes
- Slide Switch Control

**Technical Data**

Typology :	Traditional
Approval certificates :	G-Mark
Length electrical supply cord (cm) :	150
Required niche size for installation (HxWxD) :	208mm x 493.0mm x 257mm
Net weight (kg) :	4.470
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m <sup>3</sup> /h) :	300
Maximum output recirculating air (m <sup>3</sup> /h) :	300
Number of lights :	2
Noise level (dB) :	61
Diameter of air outlet (mm) :	120
Grease filter material :	Washable aluminium
Odour filter :	No
Operating Mode :	Convertible
Optional accessories :	DWZOINOAO, DWZOINOTO
Total power of the lamps (W) :	6
Grease filter type :	Kassette
Connection Rating (W) :	121
Current (A) :	5
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	GB plug
Installation typology :	Built-in
Material body :	Stainless steel
Approval certificates :	G-Mark
Plug type :	GB plug
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	10.62 x 12.79 x 32.16
Net weight (lbs) :	10.000
Gross weight (lbs) :	17.000
Motor location :	Integrated motor in hood body
No-return airflow flap :	Yes
Length electrical supply cord (cm) :	150
Dimensions of the product, with chimney (if exists) (mm) :	x 534.0 x 300.0
Dimensions of the packed product (HxWxD) (mm) :	270 x 325 x 817
Net weight (kg) :	4.470
Gross weight (kg) :	7.6



**Serie | 2, canopy cooker hood, 53 cm,  
Stainless steel  
DLN53AA50B**

**The canopy cooker hood: offers you  
flexibility in your kitchen planning - mount it  
either on the wall or above a kitchen island.**

---

**Variant:**

**Design:**

- Canopy hood

**Comfort:**

- Suitable for ducted or re-circulated extraction
- For installation in a modified cupboard, above a hob
- Sliding switch control for extractor speeds and light
- 3 speeds
- Paper grease filter with saturation indicator

**Environment and safety:**

- Energy Efficiency Class: D\*
- Average Energy Consumption: 66.7 kWh/year\*
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: D\*
- Grease Filtering Efficiency Class: D\*

**Technical information:**

- Power rating: 121 W
- Noise min./max. Normal Level: 46/61 dB\*
- Light Intensity: 78 lux
- Colour Temperature: 2700 K

**Measures:**

- 120 mm diameter pipe

**Optional accessories**

- Charcoal odour filter DHZ7304
- grease filter DHZ2100

*\* In accordance with the EU-Regulation No 65/2014*

**Serie | 2, canopy cooker hood, 53 cm,  
Stainless steel  
DLN53AA50B**

---